

DTX-MULTI 12 Version1.1

The Owner's Manual bundled with your DTX-MULTI 12 covers version 1.00 of the firmware. This firmware has now been upgraded to version 1.1, which adds several new functions. The corresponding additions and changes to the bundled Owner's Manual are described below.

To check your DTX-MULTI 12's firmware version:

While holding down the [SHIFT] button, turn on the electronic percussion pad.

“Ver : *.*” indicates the current version of the firmware.

■ Support for the DT50S/DT50K (Drum Trigger) (pages 101 and 104 of Owner's Manual)

Pad types have been added for the DT50S/DT50K.

The new trigger parameter “NoiseFilterTable” has been added.

The new trigger parameter “2P Balance” has been added.

The new setting values “14&15” and “16&17” have been added for Copy Trigger parameters “Pad to copy” and “Pad to replace.”

NOTE

For details on how to use the drum trigger DT50S/DT50K with the DTX-MULTI 12, see the Drum Trigger Module Setup Manual for DT50S/DT50K PDF document.

Yamaha Downloads: <http://download.yamaha.com>

■ Addition of new pad types (page 101 of Owner's Manual)

New types of pads are now supported as follows.

KP125W/125	XP80 Snare	TP70S HiHat
KP100	XP80 Tom	TP70
KU100	XP70	PCY100
XP120/100Sn	TP70S Snare	PCY90
XP120/100Tm	TP70S Tom	

■ Expansion of the Click-track output selection setting range (page 84 of Owner's Manual)

“ph2” setting has been added for ClkOutSel (Click-track output selection) parameter.

This setting is used to output the click-track via the PHONES jack only, and all other sound via the OUTPUT (L/MONO and R) jacks only.

■ Expansion of the input gain setting range (page 101 of Owner's Manual)

The input gain setting range is expanded.